

Better Vision Better Results

COMPLETE SYSTEM

The Redfin R3800 Endoscope Camera System is a powerful, high-definition video endoscopy system designed to handle the demands of diagnostic and surgical applications at an affordable cost.

FULL HD 1080p

High quality optics and multiple console output options allow this set to stream a live, Full HD image to any commercial or medical grade monitor. To record the live feed, the Video Console is compatible with any standard video recorder.

MOBILE

With the included carrying case, it's easy to pack up the R3800 system for remote procedures or multiple clinics.

AFFORDABLE

The Redfin R3800 delivers a superb, high quality Full HD image with an innovative mobile form factor at an extremely affordable price. Its cost enables clinics and hospitals to deploy multiple units where a single unit would normally be used.



R3800

Full HD Mobile Camera System



Endoscope Camera



- Full HD Endoscope Camera
- Waterproof Design, Fully Soakable
- Includes 22mm Universal Coupler
- Rugged Construction
- 10ft Cable Included

Video Console



- SDI and HDMI Outputs
- Available Resolutions:
 - 1080p & 720p
- Compact for Easy Portability
- Compatible with Standard Video Recorders

Better Vision Better Results

ADDITIONAL INFORMATION

For more information about the R3800 please contact:
sales@fireflyglobal.com

WARRANTY & PRODUCT SUPPORT

All Redfin products come with a one-year warranty. Product support is provided through Firefly's worldwide distribution network and also directly from its company headquarters in Massachusetts. Support is offered at no additional cost.

COMPANY BACKGROUND

Firefly has a strong history of offering high quality products to medical professionals worldwide. Known for their Wireless Devices, Firefly has expanded into Full HD Wired solutions as well. Available in over 40 countries, Firefly has established itself as the innovation leader for high quality, affordable devices.

Technical Specifications

Weight (approximate)	Camera head and cable: 300g / 0.66lbs Video Console: 544g / 1.2lbs
Camera Dimensions (approximate)	Length: 7.7cm / 3.03in Width: 4.0cm / 1.57in Height: 5.3cm / 2.08in
Console Dimensions (approximate)	Length: 16cm / 6.3in Width: 11.2cm / 4.4in Height: 4.0cm / 1.57in
Power Source	External AC/DC switching power supply Rating (AC): 100-240 VAC, 1.2A, @ 50 – 60 Hz Rating (DC): 12 VDC, 2.5A
Protection against ingress of water	Camera head and cable: IP67 Video Console: IPX0
Mounting	C-mount universal coupler
Image Sensor	CMOS sensor, 2.12 M active pixels
Console Outputs	1x HD-SDI 1x HDMI (Type A Connector)
Display Formats	1280x720 1920x1080
Operating Conditions	Temperature: 0°C to +40°C (+32°F to +104°F) Relative Humidity: 20% to 90% noncondensing
Shipping and storage conditions	Temperature: -20°C to +60°C (-4°F to +140°F) Relative Humidity: 90% noncondensing max

Specifications are subject to change in any matter and at any time without notice. The Redfin word and the Redfin logo are trademarks or trade names of Firefly Global and its affiliates in the United States and/or other countries. All rights in such names, marks or logos are reserved by Firefly Global.

Copyright © 2022 by Firefly Global, All rights reserved. Rev 2.0
www.fireflyglobal.com

Included: Carrying Case



- Protects R3800 Components
- Added space for additional cables
- Rugged, Compact, and Portable
 - Length: 48cm / 18.9in
 - Width: 33cm / 13in
 - Height: 10cm / 3.94in

Optional: LED Light Source



- Completely Wireless Operation
- Ultra-Bright LED. 6500K White
- 4+ Hour Operation
- Includes 2 Rechargeable Batteries

